# EconoScan<sup>TM</sup> III

# Short Range CCD Barcode Scanner

## High Performance at a Low Price

ID TECH is proud to introduce the EconoScan II, our next generation short range CCD scanner that is specially designed to deliver high-end performance at the lowest possible price. The scanner utilizes exceptional decoding technology, making it the best in its class in terms of performance and value.

#### **Ergonomic and Lightweight**

The EconoScan II contains no moving parts, yet it is exceptionally lightweight and designed to fit comfortably in the hand for extended periods of usage. This ergonomic hand-held scanner is ideal to be used in a wide variety of markets, including retail, logistics and light industry applications.

### **High-Speed Contact Scanning**

The EconoScan enables quick contact scanning of bar codes up to 4 inches in length. With an impressive scan rate of 200 scans per second, low-quality or damaged bar codes as well as small or high-density bar codes can be read with exceptional speed and accuracy.

#### **Features and Benefits:**

- Super slim body design
- The longest reading range in its class
- High scan rate of 200 scans/sec
- Supports most linear barcode symbologies
- Data formatting features
- Continuous and flash scanning mode





# EconoScan™ // Specifications IDBA-42X4SR

### **Electrical**

Power Requirements:  $5.0 \text{ VDC} \pm 5\%$ 

Interfaces: PS/2, RS232, USB Keyboard
Light Source: 660 nm visible red LED
Sensor: 2500 pixel CCD

#### **Environmental**

 $\begin{array}{ll} \mbox{Operating Temperature:} & \mbox{O°C to } 50\mbox{°C (} 32\mbox{°F to } 122\mbox{°F}) \\ \mbox{Storage Temperature:} & -26\mbox{°C to } 60\mbox{°C (} -14.8\mbox{°F to } 140\mbox{°F}) \\ \mbox{Humidity:} & 10\% - 80\% \mbox{ relative humidity} \end{array}$ 

Drop Test: 3.94 feet (1.2 m)

### Mechanical

Dimensions: 6.10 inches (155 mm) x 3.07 inches (78 mm) x 0.63 inches (16 mm)

Weight: 3.0 oz. (without cable)
Indicator: LED, beep tone
Color: Beige

Field Width: 5.59 inches (142mm) for 10.5 mil code 39 at 175mm from the lens plate

Resolution: 0.1 mm (4 mils)
PCS: 45% or more
Scan Rate: 200 scans per second

Range: 0 inches (0 cm) to 4 inches (10.15 cm)

Symbologies: Code 39, Full ASCII Code 39, Code 32, Code 128, Code 93, Code 11, Codabar/NW7,

All UPC/EAN/JAN Code (EAN-13, EAN-8, UPC-A, EPC-E, EAN-128), Interleave 2 of 5, STD 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Chinese Postage Code, MSI/PLESSY,

Italian Pharmacy Code (RSS, GS1 available 2010)

Approvals: FCC Part15 Class B, CE EMC Class B



#### Corporate Headquarters:

10721 Walker Street, Cypress, California 90630 www.idtechproducts.com (714) 761-6368 sales@idtechproducts.com

#### International Sales Office Canada & South America:

+450 465 5261 (Canada) robertop@idtechproducts.com

#### **European Sales Offices:**

+49(0) 8851 6159900 (Germany) emea@idtechproducts.com

ISO 9001 Certified

